

## Top Tec 4600 5W-30

### Description

Modern top class low-friction engine oil for all-season use in gasoline and diesel engines with or without diesel particulate filters (DPF) and exhaust-gas turbochargers. The combination of unconventional basic oils using synthetic technology, together with the latest additive technology, guarantee a motor oil that provides exceptional protection against wear and reduces oil and fuel consumption, while ensuring that the engine is immediately supplied with oil. This product allows for oil change intervals of up to 40,000 km, depending on the manufacturer's specifications. In addition, Top Tec 4600 5W-30 is best suitable for gas fuelled (CNG/LPG) passenger cars.

### Properties

- excellent wear protection
- high lubrication reliability
- long engine service life
- especially suitable for vehicles with diesel particulate filter
- reduces pollutant emissions
- tested for turbochargers and catalytic converters
- smooth engine running
- instant lubrication after cold start
- reduces fuel consumption
- optimum oil pressure under all operating conditions
- high shear stability
- optimum stability to aging
- outstanding engine cleanliness
- miscible with all commercially available motor oils

### Specifications / Approvals

ACEA C2 • ACEA C3 • API SN • BMW Longlife-04 • MB-Approval 229.31 • MB-Approval 229.51 • MB-Approval 229.52 • Opel OV 040 1547 - D30 • VW 505 00 • VW 505 01

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required**

Fiat 9.55535-S3 • Ford WSS-M2C 917-A • GM dexos2 • GWM • HAVAL • Opel GM-LL-A-025 • Opel GM-LL-B-025 • Wuling

### Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,85 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	68,9 mm <sup>2</sup> /s ASTM D 7042-04



### Technical data

Viscosity at 100 °C	12 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≥ 6600 mPas ASTM D5293
Viscosity index	172 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	10 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,4 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	2,5 DIN ISO 2049

### Areas of application

Optimum for modern gasoline and diesel engines with multi-valve technology, Valvetronic and turbocharging (with or without charge air cooling). Especially suitable where there are long intervals between oil changes and heavy duty engine requirements.

### Application

The operating instructions of the vehicle and engine manufacturers must be followed.

**Full effectiveness can only be ensured when the product is not mixed!**

### Available pack sizes

1 l Canister plastic	2315 BOOKLET
4 l Canister plastic	3763 BOOKLET

## Top Tec 4600 5W-30

### Available pack sizes

5 l Canister plastic	2316
	BOOKLET
20 l Canister plastic	3757
	D-GB-I-E-P
60 l Black plate barrel	3758
	D-GB
205 l Black plate barrel	3759
	D-GB
1.000 l Container	21619
	D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**